




# NTA BEARING PRECISION AXLE CORP.



NUP-304 Bearing 2D drawings and 3D CAD models

0.787 Inch | 20 Millimeter x 2.047 Inch | 52  
 Millimeter x 0.591 Inch | 15 Millimeter  
**CONSOLIDATED BEARING NUP-304**  
 Cylindrical Roller Bearings

Bearing No. NUP-304

|                           |   |
|---------------------------|---|
| Category                  | Cylindrical Roller Bearings   |
| Inventory                 | 0.0   |
| Manufacturer Name         | CONSOLIDATED BEARING  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 0.156   |
| EAN                       | 0644075057424   |
| Product Group             | B04144  |
| Bore Profile              | Straight  |
| Cage Material             | Steel   |
| Precision Class           | RBEC 1   ISO P0   |
| Number of Rows of Rollers | Single Row  |
| Separable                 | No  |
| Rolling Element           | Cylindrical Roller Bearing  |
| Profile                   | Complete with Outer and Inner Ring  |
| Snap Ring                 | No  |
| Internal Clearance        | C0-Medium   |
| Retainer                  | Yes   |
| Relubricatable            | Yes   |
| Inch - Metric             | Metric  |
| Other Features            | Steel or Glass Fiber Cage   1 Rib Inner Ring with Side Plate   2 Rib Outer Ring   Cage on Outer Ring ID |
|                           |   |



## NTA BEARING PRECISION AXLE CORP.

|                          |   |
|--------------------------|---|
| Long Description         | 20MM Bore; Straight Bore Profile; 52MM Outside Diameter; 15MM Width; Steel Cage Material; RBEC 1   ISO P0; Single Row; Not Separable; No Snap Ring; Relubricatable; C0-Medium Internal Clearance; Retai |
| Category                 | Cylindrical Roller Bearing  |
| UNSPSC                   | 31171547  |
| Harmonized Tariff Code   | 8482.50.00.00   |
| Noun                     | Bearing   |
| Manufacturer URL         | <a href="http://www.consbrgs.com">http://www.consbrgs.com</a>   |
| Manufacturer Item Number | NUP-304   |
| Weight / LBS             | 0.344   |
| D                        | 2.047 Inch   52 Millimeter  |
| B                        | 0.591 Inch   15 Millimeter  |
| d                        | 0.787 Inch   20 Millimeter  |